


Kompakte funktionssichere Verteilerbox *Compact reliable distribution box*



Kompakte robuste Verteilerbox mit 360° Schirmung und mit variablen Anschlussoptionen

Die kompakte Verteilerbox überzeugt zum einen durch Flexibilität und ist für jede Applikation maßgeschneidert durch verschiedene Anschlussoptionen und die Erweiterungsmöglichkeiten (Duplizierung) der Basisversion mittels eines Adapters. Zum andern sichert dieses Verteilersystem durch sein spezielles Design mit Vollmetallgehäuse und vibrationsichere Crimptechnik als Anslusstechnik hohe Funktionssicherheit.

Technische Merkmale

- 360° Schirmung durch spezielles Vollmetallgehäuse-Design
- Plug&Play mit steckbarem M12 Anschluss-Stift oder Buchse für die Codierungen A, B, D, A-8
- Crimpflansch/Crimphülse für torsions- und vibrationsicheren Kabelschirmanschluss und Zugentlastung
- Kabelklemme für Sonderkabel mit einem Außendurchmesser von bis zu 14mm
- Knickschütztülle für kostengünstigen Kabelanschluss ohne Sonderanforderungen
- Basisversion mit 5 Ein-/Ausgängen
- Blindstopfen für den Verschluss nicht genutzter Ein-/Ausgänge
- Erweiterung mit einem Adapter auf Verteilerboxen mit hoher Anzahl Ein-/Ausgänge: Anzahl der Basisversion x 4
- Version mit 2 integrierten Befestigungslaschen für die Wand

Compact robust distribution box and with variable connection options

The compact distribution system convinces on the one hand by its flexibility and is tailor-made for every application with the expansion options (duplication) of the basic version by means of an adapter. On the other hand, this distribution system ensures high reliability through its special design with full metal housing and vibration-proof crimp technology as connection technology.

Technical features

- 360° shielding due to special full metal housing design
- Plug & play with M12 connection male or female for the codings A, B, D, A-8 or M8 upon request
- Crimp flange / crimp sleeve for cable shield connection and strain relief torsion- and vibration-proof
- Cable clamp for special cables with an outer diameter of up to 14mm
- Cable bushing for cost-effective cable connection without special requirements
- Basic version with 5 inputs / outputs
- Blanking plug for closing unused inputs / outputs
- Extension with an adapter on distribution boxes
Number of inputs / outputs: Number of basic versions x 4
- Version with 2 integrated fastening straps for the wall